



Absorptive Coaxial SP2T Switch 0.1-40GHz

Features

- Ultra Wide Band Operation 0.1-40GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Customization available upon request



Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT
Fiber Optics

Parameters	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	0.1		8	8		26.5	26.5		40	GHz
Insertion Loss		2.8	3.5		4.0	4.5		4.5	5.0	dB
Insertion Loss Temperature Coefficient		0.003			0.003			0.003		dB/ °C
Isolation	50	60		50	60		45	55		dB
Input VSWR		2.5			2.5	2.8		1.8	2.5	: 1
Output VSWR		2.5			2.5	2.8		1.8	2.5	: 1
RF Input Power			23			23			23	dBm
DC Power Dissipation		0.6			0.6			0.6		W
0.1dB Compression Point (P0.1dB)		23			23			23		dBm
IIP3		55			54			50		dBm
Switching Speed		50	100		50	100		50	100	ns
Weight	0.71									ounces
Impedance	50									Ω
Bias Current (+5V / -5V)	110/50									mA
Input / Output Connectors	2.92mm-Female									
Finish	Gold Plated									
Material	Aluminum									
Sealing	Hermetically Sealed (optional)									



Absolute Maximum Ratings

Biasing	+5V $\pm$ 10%/-5V $\pm$ 10%
---------	-----------------------------

Ordering Information


Part No.	Description
DBSA0200104000A	SP2T 0.1-40GHz PIN Diode Switch

Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)




Truth Table


TTL Control Voltage THRESHOLD	Low(0)=0~0.8V
	High(1)=2.8~5V
Control Input TTL	Signal Path State
0	J0-J2
1	J0-J1
Control Pin Customization available upon request	




Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-40°C




Input VSWR @-40°C



Output VSWR @-40°C




Isolation @-40°C







Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C



Isolation @+85°C



Switching Speed



Switching Speed

