




Absorptive 2-4GHz Coaxial SP2T Switch

Features

- Wide Band Operation 2-4GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Customization available upon request



Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT
Fiber Optics

Parameters	Min	Typ.	Max	Units
Frequency Range	2		4	GHz
Insertion Loss		1.1	1.3	dB
Insertion Loss Temperature Coefficient		0.003		dB/ ° C
Isolation	70	85		dB
Input VSWR		1.3	1.5	: 1
Output VSWR		1.3	1.5	: 1
RF Input Power (CW)			5	W
DC Power Dissipation		1		W
0.1dB Compression Point (P0.1dB)		37		dBm
IIP3		55		dBm
Switching Speed		300	500	ns
Weight	1.8 Max.			ounces
Impedance	50			Ω
Bias Current (+5V)	200			mA
Input / Output Connectors	SMA - Female			
Finish	Gold Plated			
Material	Aluminum			
Sealing	Hermetically Sealed (Optional)			

Absolute Maximum Ratings

Biasing Voltage	+5V±10%
-----------------	---------

Ordering Information


Part No.	Description
DBSA0202000400G	SP2T 2-4GHz PIN Diode Switch

Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions


Outline Drawing:

All Dimensions in mm (inches)







Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-40°C




Input VSWR @-40°C



Output VSWR @-40°C




Isolation @-40°C







Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C



Switching Speed



Switching Speed





RFecho
A Gateway to RFWorld