


Reflective 2-20GHz Coaxial SP4T Switch

Features

- Wide Band Operation 2-20GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Customization available upon request



Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT
Fiber Optics

Parameters	Min	Typ.	Max	Min	Typ.	Max	Min	Typ.	Max	Units
Frequency Range	2-8			8-12			12-20			GHz
Insertion Loss		1.4	2.0		1.8	2.5		2.8	3.5	dB
Insertion Loss Temperature Coefficient		0.003			0.003			0.003		dB/ °C
Isolation	75	80		75	80		70	80		dB
Input VSWR		1.6	1.8		1.6	1.8		1.6	1.8	: 1
Output VSWR		1.6	1.8		1.6	1.8		1.6	1.8	: 1
RF Input power (CW)			30			30			30	dBm
DC Power Dissipation		0.8			0.8			0.8		W
0.1dB Compression Point(P0.1dB)		30			30			30		dBm
IIP3		55			55			55		dBm
Switching Speed		100			100			100		ns
Weight	1.06									ounces
Impedance	50									Ω
Bias Current (+5V / -5V)	160/50									mA
Input / Output Connectors	SMA-Female									
Finish	Gold Plated									
Material	Aluminum									
Sealing	Hermetically Sealed (optional)									



Absolute Maximum Ratings

Biasing	+5V±10%/-5V±10%
---------	-----------------

Ordering Information


Part No.	Description
DBSR0402002000B	SP4T 2-20GHz PIN Diode Switch

Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)




Truth Table


TTL Control Voltage THRESHOLD	Low(0)=0~0.8V	
	High(1)=2.8~5V	
Control Input TTL		Signal Path State
C2	C1	
0	0	J0-J1
0	1	J0-J2
1	0	J0-J3
1	1	J0-J4
Control Pin Customization available upon request		




Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-40°C




Input VSWR @-40°C



Output VSWR @-40°C




Isolation @-40°C







Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C



Isolation @+85°C



Switching Speed



Switching Speed

