OG103B-1930-1995



Features

- Surface-mount construction
- Frequency range: 1930–1995 MHz
- Isolation: 22 dB
- Insertion loss: 0.25 dB
- Forward power: 100 W

Description


The OG103B-1930-1995 is a surface-mount isolator for 1930–1995 MHz. It routes reflected RF power into its termination. The forward and reverse power ratings are listed on page 2.

RFecho is trademark of Ocean Microwave
All rights reserved.
©RFecho 2025

Technical indicators

Frequency	Return loss	Isolation	Insertion loss	IMD3	Forward power
1930–1995 MHz	22 dB	22 dB	0.25 dB	-65 dBc at 2 × 20W	100 W
Reverse power			**Operating temp.**		
30 W			-40 to 105 °C		


Mechanical dimensions



RFecho is trademark of Ocean Microwave
All rights reserved.
©RFecho 2025

RF performance


Manufacturer test trace | Catalog page 21



RFecho is trademark of Ocean Microwave
All rights reserved.
©RFecho 2025

RF performance


Manufacturer test trace | Catalog page 21



RFecho is trademark of Ocean Microwave
All rights reserved.
©RFecho 2025

RF performance


Manufacturer test trace | Catalog page 21



RFecho is trademark of Ocean Microwave
All rights reserved.
©RFecho 2025

RF performance

Manufacturer test trace | Catalog page 21



RFecho is trademark of Ocean Microwave
All rights reserved.
©RFecho 2025