



## SPECIFICATIONS

|                    |             |
|--------------------|-------------|
| Frequency Range:   | 2.0-18.0GHz |
| Insertion Loss:    | 1.5 dB Max  |
| Isolation:         | 18dB Min    |
| Amplitude Balance: | 0.4dB Max   |
| Phase Balance:     | 10.0° Max   |
| VSWR:              | 1.60:1 Max  |

### Notes:

1. Power rating is 30 watts max. for load VSWR better than 1.20:1

|   |  |  |  |
|---|--|--|--|
|   |  | OCEAN MICROWAVE CORPORATION<br>1209 Caifuxihuan 58 NO. Caihuying Bridge,Fengtai<br>District,Beijing/China<br>Tel: + 86-10-60290088   Fax: + 86-10-63497801<br><a href="http://www.ecmicrowave.com">http://www.ecmicrowave.com</a>  <br><a href="http://www.oceanmicrowave.com">http://www.oceanmicrowave.com</a> |  |
|   |  | DESCRIPTION: <b>Power Divider</b>  |  |
| MODEL NO. : <b>OPD-3- 20180S</b>                    |  | SIZE:      CAGE CODE:      REV CODE:   |  |
| DIMENSIONS ARE IN MILLEMETERS<br>DECIMAL TOLERANCE: |  | SCALE: N / A   | ALL SPECIFICATIONS ARE SUBJECT TO<br>CHANGE WITHOUT NOTICE AT ANY TIME |
|   |  | <b>SHEET 1 OF 1</b>  |  |