



Wide Band Low Noise Amplifier 5GHz ~ 10GHz

Features

- Gain: 20dB Typical
- Noise Figure: 2.0dB Typical
- P1dB Output Power: +16dBm Typical
- Supply Voltage: +4V @ 80mA
- 50 Ohm Matched



Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT
Fiber Optics

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.
Frequency Range	5		7.5	7.5		10	GHz
Gain	18	20		18	20		dB
Gain Flatness		± 0.7	± 1.0		± 0.6	± 1.0	dB
Gain Variation Over Temperature (-40 ~ +85)		± 0.5			± 0.5		dB
Noise Figure		2.0	2.6		2.0	2.8	dB
Input VSWR		1.8	2.2		1.8	2.0	: 1
Output VSWR		1.6	2.0		1.6	2.0	: 1
Output 1dB Compression Point (P1dB)	14.5	16		14.5	16		dBm
Saturated Output Power (Psat)		18			18		dBm
Output Third Order Intercept (OIP3)		27			27		dBm
Supply Current (Vcc=+4V)		80	100		80	100	mA
Isolation S12		-32			-33		dB

Weight	0.35ounces	Impedance	50 ohms
Input /Output Connectors	SMA-Female	Material	Aluminum
Finish	Gold Plated	Package Sealing	Epoxy Sealed (Standard)
			Hermetically Sealed (Option with extra charge)

Environmental Specifications


Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Power OFF Procedure

Step 1	Turn off +4V biasing
Step 2	Remove RF connection
Step 3	Remove Ground


All Dimensions in mm (inches)

Heat Sink required during operation(Sold Separately)







Gain @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Gain @-40°C




Input VSWR @-40°C



Output VSWR @-40°C




Isolation @-40°C







Gain @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C




Gain vs. Output Power




P1dB vs. Frequency



Output Third Order Intercept (OIP3)




Saturation Power vs. Frequency







Noise Figure



2nd Harmonic Wave Output Power



3rd Harmonic Wave Output Power



4th Harmonic Wave Output Power

