




Ultra Wide Band Low Noise Amplifier 1GHz~11GHz

Features

- Gain: 17dB Typical
- Noise Figure: 1.6dB Typical
- P1dB Output Power: +18dBm Typical
- Supply Voltage: +5V @ 70mA
- 50 Ohm Matched



Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT
Fiber Optics

Parameters	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	1		6	6		11	GHz
Gain	15	17		14	16		dB
Gain Flatness		±0.5	±1.0		±0.5	±1.0	dB
Gain Variation Over Temperature (-40 to +85)		±1.0			±1.0		dB
Noise Figure		1.6	2.2		2.0	2.5	dB
Input VSWR		1.5	2.0		1.6	2.0	: 1
Output VSWR		1.4	1.8		1.4	1.8	: 1
Output 1dB Compression Point (P1dB)	15	18		14	16		dBm
Saturated Output Power (Psat)		19			17.5		dBm
Output Third Order Intercept (OIP3)		29			28		dBm
Supply Current (Vdd=+5V)		70	85		70	85	mA
Isolation S12		-25			-27		dB

Weight	0.71ounces	Impedance	50ohms
Input /Output Connectors	SMA-Female	Material	copper
Finish	Gold Plated	Package Sealing	Epoxy Sealed (Standard)
			Hermetically Sealed (Option with extra charge)



Absolute Maximum Ratings

Operating Voltage	+5.5V
RF Input Power (RFIN)	5dBm

Biasing Up Procedure

Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect -5V biasing
Step 4	Connect +5V biasing

Power OFF Procedure

Step 1	Turn off +5V biasing
Step 2	Turn off -5V biasing
Step 3	Remove RF connection
Step 4	Remove Ground.


Environmental Specifications

Operational Temperature	-45°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Outline Drawing:


All Dimensions in mm (inches)

Heat Sink required during operation(Sold Separately)







Gain




Input VSWR




Output VSWR




Isolation



Gain vs. Output Power




P1dB vs. Frequency







Output Third Order Intercept (OIP3)




Noise Figure




Noise Figure



2nd Harmonic Wave Output Power



3rd Harmonic Wave Output Power



4th Harmonic Wave Output Power

