




Low Noise Amplifier 2.4GHz~6GHz

Features

- Gain:42dB Typical
- Noise Figure: 2.2dB Typical
- P1dB Output Power: +20dBm Typical
- Functional Bandwidth : 0.5GHz – 6GHz
- Supply Voltage: +12V
- 50 Ohm Matched Input / Output



Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT
Fiber Optics

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	0.5		2.4	2.4		6	GHz
Gain	38	42		38	42		dB
Gain Flatness		± 1.0	± 1.5		± 0.5	± 1.5	dB
Gain Variation Over Temperature (-40°C~+85°C)		± 1.0			± 1.0		dB
Noise Figure		2.8	4.0		2.2	4.0	dB
Input VSWR		1.6			1.8		: 1
Output VSWR		1.6			1.6		: 1
Output Power for 1 dB Compression (P1dB)	20	22		17	20		dBm
Saturated Output Power (Psat)		24			22		dBm
Output Third Order Intercept (IP3)		30			30		dBm
Supply Current (Vcc=+12V)		280	300		280	300	mA
Isolation S12		-65			-65		dB

Weight	1.06ounces	Impedance	50ohms
Input / Output Connectors	SMA-Female	Material	Aluminum
Finish	Gold Plated	Package Sealing	Epoxy Sealed (Standard)
			Hermetically Sealed (Option with extra charge)



Absolute Maximum Ratings

Operating Voltage	+15V
RF Input Power (RFIN)	-2dBm

Biasing Up Procedure

Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect +12V biasing

Power OFF Procedure

Step 1	Turn off +12V biasing
Step 2	Remove RF connection
Step 3	Remove Ground


Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Outline Drawing:


All Dimensions in mm (inches)

Heat Sink required during operation(Sold Separately)







Gain @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Gain @-40°C




Input VSWR @-40°C



Output VSWR @-40°C




Isolation @-40°C







Gain @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C




Gain vs. Output Power




P1dB vs. Frequency



Current




Output Third order Intercept (OIP3)







Noise Figure(0.5-4GHz)




Noise Figure(4-6GHz)



2nd Harmonic Wave Output Power



3rd Harmonic Wave Output Power



4th Harmonic Wave Output Power

