




# Medium Power Wide Band Driver Amplifier 30GHz~65GHz

## Features

- Gain: 38dB Typical
- Saturated Output Power: +22dBm Typical
- Supply Voltage: +12V



## Typical Applications

- Wireless Infrastructure
- 5G communication
- Test and measurement Instrument

RF Microwave & VSAT  
Fiber Optics

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	30		40	40		60	60		65	GHz
Gain	30	36	40	33	38	43	24	30	40	dB
Gain Flatness		±2.5			±3.0			±5.0		dB
Gain Variation Over Temperature (-40°C~+85°C)		±3.0			±3.0			±3.0		dB
Input VSWR		2.0	3.0		2.5	3.5		2.0	3.0	: 1
Output VSWR		2.5	3.5		2.5	3.5		2.0	3.0	: 1
Output 1dB Compression Point (P1dB)	16	20		17	21		15	18		dBm
Saturated Output Power (Psat)		21			22			19		dBm
Output Third Order Intercept (OIP3)		26			28			25		dBm
Supply Current (Vcc=+12V)		450	1000		450	1000		450	1000	mA
Isolation S12		-70			-60			-55		dB

Weight	4.6 max. ounces	Impedance	50ohms
Input / Output Connectors	1.85mm-Female	Material	Aluminum
Finish	Gold Plated	Package Sealing	Epoxy Sealed (Standard)
			Hermetically Sealed (Optional)



### Absolute Maximum Ratings

Operating Voltage	+15V
RF Input Power (RFIN)	-8dBm

### Biasing Up Procedure

Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect +12V biasing

### Power OFF Procedure

Step 1	Turn off +12V biasing
Step 2	Remove RF connection
Step 3	Remove Ground


### Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

### Outline Drawing:


All Dimensions in mm (inches)

Heat Sink required during operation(Sold Separately)







### Gain@+25°C




### Input VSWR@+25°C




### Output VSWR@+25°C




### Isolation@+25°C



### Gain@-40°C




### Input VSWR@-40°C







### Output VSWR @-40°C




### Isolation @-40°C




### Gain @+85°C




### Input VSWR @+85°C



### Output VSWR @+85°C




### Isolation @+85°C







### Output VSWR @+85°C




### Isolation @+85°C




### Gain vs. Output Power



### P1dB vs. Frequency



### Saturation Power vs. Frequency



### Output Third Order Intercept (OIP3)

